

Ururu streamer technology air purifier

MCK70YV



Humidification



Flash Streamer

Humidification and air purification in one

- › Air purification for large spaces such as residential and light commercial applications
- › Pure air thanks to Daikin 'Catch and Clean' approach in decomposing harmful substances
- › High performance electrostatic HEPA filter with no need to change for 10 years
- › Whisper quiet

MCK70YV




MCK70YV-YB

Indoor Unit			MCK	70YV
Application				Floor standing type
Applicable room area			m ²	48 (1) / 96 (2) / 375 (3)
Dimensions	Unit	HeightxWidthxDepth	mm	600 x395 x287
Weight	Unit		kg	12.5
Casing	Colour			White (N9.0)
Fan	Type			Multi Blade Fan (Sirocco fan with shroud assembly)
	Air flow rate	Air purifying operation	Silent/Low/Medium/Turbo	m ³ /h 60 /132 /210 /420
		Humidifying operation	Silent/Low/Medium/Turbo	m ³ /h 102 /132 /210 /420
Sound pressure level	Air purifying operation	Silent/Low/Medium/Turbo	dBA	18 /27 /37 /54
	Humidifying operation	Silent/Low/Medium/Turbo	dBA	23 /27 /37 /54
Humidifying operation	Power input	Silent/L/M/Turbo	kW	0.011 /0.012 /0.018 /0.068
	Humidification	Turbo	ml/h	650
	Water tank capacity		l	3.6
Air purifying operation	Power input	Silent/L/M/Turbo	kW	0.008 /0.010 /0.016 /0.066
Deodorizing method				Flash streamer + Deodorizing catalyst
Dust collecting method				Electrostatic HEPA filter
Air filter	Type			Polyethylene terephthalate net
Sign	Item	01		Dust sensor lamp: 3 stages // PM 2.5 sensor lamp: 3 stages / Odour sensor lamp: 3 stages // Humidity monitor : 20% - 90% / Humidity setting: Low/Standard/High / Airflow rate: Quiet/Low/Standard/Turbo / AUTO FAN mode / Econo mode / Anti-pollen mode / MOIST mode / CIRCULATION mode / Water supply lamp / Streamer lamp / Recommendation mode lamp / Humidifier ON/OFF lamp / Sleep mode / Child proof lock lamp
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220-230
Type				Humidifying air purifier

(1) The coverage area is appropriate for operating the unit of maximum fan speed (HH). Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. | (2) Converted to NRCC standards from test values in accordance with JEM1467. | (3) Converted to CADR standards from test values in accordance with JEM1467. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Electrostatic HEPA filter and humidifying filters are attached in the unit. | Requirements according to JEM1467.

Daikin Europe Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · <https://www.daikin.eu> · RPR Oostende (Responsible Editor)



ECPEN21-745A

11/2021

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.



Daikin MCK70YV čistička vzduchu

MCK70YVM					
Type					Zvlhčovacia čistička vzduchu
Použitie					Parapetný typ
Casing	Colour				Biele (N9. 0)
Vonkajšie rozmery	Jednotka		Výška	mm	600 (5)
			Šírka	mm	395
			Hĺbka	mm	287
Hmotnosť	Jednotka			kg	12.5
Použiteľná oblasť v miestnosti	m ²				48 (1), 96 (2), 375 (3)
Prevádzka čističky vzduchu	Vstup napájania		Turbo	kW	0.066
			M	kW	0.016
			L	kW	0.010
			Tichý	kW	0.008
Prevádzka zvlhčovania	Vstup napájania		Turbo	kW	0.068
			M	kW	0.018
			L	kW	0.012
			Tichý	kW	0.011
	Kapacita nádrže na vodu			l	3.6
Hladina akustického tlaku	Prevádzka čističky vzduchu		Turbo	dBA	54
			Stredný	dBA	37
			Nízka	dBA	27
			Tichý	dBA	18
	Prevádzka zvlhčovania		Turbo	dBA	54
			Stredný	dBA	37
			Nízka	dBA	27
			Tichý	dBA	23
Ventilátor	Prietok vzduchu	Prevádzka čističky vzduchu	Turbo	m ³ /h	420
			Stredný	m ³ /h	210
			Nízka	m ³ /h	132
			Tichý	m ³ /h	60
		Prevádzka zvlhčovania	Turbo	m ³ /h	420
			Stredný	m ³ /h	210
			Nízka	m ³ /h	132
			Tichý	m ³ /h	102
Dust collecting method					Elektrostatický filter HEPA
Deodorizing method					Flash Streamer + deodorizačný katalyzátor
Štandardné príslušenstvo	Elektrostatický filter HEPA				1
	Odvlhčovací filter				1
	Deodorizačný filter				1
	Návod na prevádzku				1
	Kotúč				4
Napájací kábel	m				2.0
Power supply	Phase				1~
	Frekvencia			Hz	50/60
	Napätie			V	220-240/220-230

Poznámky

- (1) - Hodnota pre vhodnú plochu pokrytia platí pre prevádzku jednotky s maximálnou rýchlosťou ventilátora (HH). Oblasť pokrytia určuje priestor, z ktorého môžete do 30 minút odstrániť určité množstvo prachových častíček.
- (2) - Premenené na štandardy NRCC z testovacích hodnôt podľa JEM1467.
- (3) - Premenené na štandardy CADR z testovacích hodnôt podľa JEM1467.
- (4) - Množstvo zvlhčovania sa mení podľa vnútornej a vonkajšej teploty a vlhkosti. Podmienky merania: teplota 20 °C, vlhkosť 30 %.
- (5) - Akustické prevádzkové výkony sú priemerné hodnoty namerané vo vzdialenosti 1 m od prednej, ľavej, pravej a hornej strany jednotky. (rovnajú sa hodnotám v bezodrazovej miestnosti)
- (6) - Elektrostatický filter HEPA a odvlhčovacie filtre sú namontované v jednotke.